



MATERIAL SAFETY DATA SHEET

IDENTIFICATION

PRODUCT(S): INDUSTRIAL LACQUER BLACK

Supplier: Concept Paints
Address: Lot 40 Charles Street St Marys 2760
Telephone Number: +61 2 96732555
Emergency Telephone: +61 2 96732555 (Monday to Friday 8am to 5pm)
Recommended Use: Industrial Coating

HAZARDS IDENTIFICATION

Classification:

- HAZARDOUS SUBSTANCE.
- DANGEROUS GOODS.
- HARMFUL.

According to the criteria of ASCC/NOHSC and the ADG Code.

Risk Phrases: R20/21 Harmful by inhalation and in contact with skin. R38 Irritating to skin. R10 Flammable.

Safety Phrases: S7/9 Keep container tightly closed and in a well-ventilated place. S16 Keep away from sources of ignition – No smoking. S24/25 Avoid contact with skin and eyes. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S29 Do not empty into drains. S33 Take precautionary measures against static discharge. S36/37/39 Wear suitable protective clothing and eye/face protection. S41 In case of fire and/or explosion do not breathe fumes. S45 In the case of accident or if you feel unwell, seek medical advice immediately. S53 Avoid exposure – obtain special instructions before use.

INGREDIENTS

| Chemical Entity / Hazardous Component | CAS Numbers | Proportion by wt. |
|---------------------------------------|-------------|-------------------|
| Xylene | 1330-20-7 | 30 - 60% |
| Acetone | 67-64-1 | 10 - <30% |
| Cyclohexanone | 108-94-1 | <10% |
| Methyl Isobutyl Ketone | 108-10-1 | <10% |
| Ethyl Alcohol | 64-17-5 | <10% |
| Methoxy Propyl Acetate | 108-65-6 | <10% |
| Ethyl Benzene | 100-41-4 | <10% |
| Carbon Black | 1333-86-4 | <10% |

This product(s) also contains other ingredients, that are not classified as hazardous by ASCC/NOHSC criteria.

FIRST AID MEASURES

Route of Exposure First Aid Measures

Ingestion: Give a glass of water. Do NOT induce vomiting. Place patients head downwards if vomiting occurs, to prevent it entering lungs .As aspiration of material into lungs can be fatal, causing chemical pneumonitis. Seek medial aid.

Eye: Immediately irrigate with large quantities of water for at least 15 minutes. Seek medical advice.

Skin: Wash exposed area thoroughly with soap and water. Remove contaminated clothing.

Inhaled: Give fresh air, careful not to become a casualty yourself. Remove and loosen clothing. If breathing normally make patient comfortable and keep warm till recovered. If breathing is difficult ensure airways are clear and have a qualified person give oxygen from a face mask. If breathing has stopped commence (EAR), if cardiac arrest commence (CPR) and seek medical aid urgently.

Advice To Doctor: Treat Symptomatically.

FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Foam, Carbon Dioxide or Dry Chemical Powder.

Hazards from Combustion Products: When burning toxic materials such as carbon monoxide, carbon dioxide and various hydrocarbons may form.

Precautions for Firefighters: Heating can cause rupture of containers with explosive force. If safe do so, remove containers from the path of the fire and keep cool with water spray.

Firefighters should wear self contained breathing apparatus with a full face and operated in the positive pressure mode.

Hazchem Code: 3[Y]E

ACCIDENTAL RELEASE MEASURES

Emergency Procedures: In the case of a spill extinguish all ignition sources and shut off the source of the spill. Ventilate the area and wear the correct Personal Protective Equipment.

Containment: Contain and absorb the spill with absorbent material such as sand, soil or vermiculite. Prevent its entry into drains. Transfer the material into drums, using non-sparking tools. Seal and label the drums. Contact the appropriate waste management authority for disposal.

HANDLING AND STORAGE

Handling: Wear the correct Personal Protective Equipment when using this product. Only use in a well ventilated area and apply the product in a spray paint booth with an adequate exhaust system.

Never eat, drink or smoke whilst handling this product. Always wash hands before smoking, eating, drinking or using the toilet.

Safe Storage: Store containers in a cool place and out of direct sunlight. Store in a well ventilated area and away sources of ignition, oxidising agents and/or foodstuffs. Keep containers tightly closed when not in use and check regularly for leaks.

EXPOSURE CONTROLS / PERSONAL PROTECTION

| Exposure Limits: | TLV –TWA (mg/m ³) |
|------------------------|-------------------------------|
| Xylene | 350 |
| Acetone | 1185 |
| Cyclohexanone | 100 |
| Methyl Isobutyl Ketone | 205 |
| Ethyl Alcohol | 1880 |
| Methoxy Propyl Acetate | 274 |
| Ethyl Benzene | 434 |
| Carbon Black | 3.0 |

Engineering Controls: Ensure sufficient ventilation to maintain concentration below exposure standard. Only use in a well ventilated area and apply the product in a spray paint booth with an adequate exhaust system. Keep containers sealed when not in use. Earth any mixing vessels when using this product.

Personal Protection: Skin contact should be avoided by wearing impervious work clothing, boots and Neoprene or PVC gloves. Eyes should be protected by chemical goggles or safety glasses fitted with side shields. If an inhalation risks exists, an organic vapour respirator or a self contained breathing apparatus with a full face and operated in the positive pressure mode, should be used. Ensure cartridges are correct for the potential air contamination.

PHYSICAL AND CHEMICAL PROPERTIES

| | |
|----------------------|----------------------------------|
| Appearance: | Black viscous liquid. |
| Odour: | Strong solvent odour. |
| pH: | Not applicable. |
| Vapour Pressure: | 24.7 kPa @ 20°C |
| Vapour Density: | Not Available |
| Boiling Point Range: | 56 – 156 °C |
| Melting Point: | Not Applicable |
| Solubility In Water: | Not Available |
| Specific Gravity: | 0.85 – 0.95 |
| Flammability Limits: | 1 (LEL) to 12.8% (UEL) by volume |
| Flash Point: | -18 °C (Open Cup) |

STABILITY AND REACTIVITY

Chemical Stability: Stable under ordinary conditions of use and storage.

Conditions to Avoid: Avoid all ignition sources.

Incompatible Materials: None

Hazardous Decomposition Products: When burning toxic materials such as carbon monoxide, carbon dioxide and various hydrocarbons may form.

Hazardous Reactions: Not Applicable.

TOXICOLOGICAL INFORMATION

Acute Health Effects:

Ingestion: Can result in headaches, nausea, vomiting and diarrhoea.

Eye: Will cause discomfort and may cause redness, itching or blurred vision.

Skin: May cause irritation to skin.

Inhaled: Vapour concentrations above exposure limits may be irritating to the eyes and respiratory tract, may cause headaches and dizziness. Prolonged exposure may result in unconsciousness.

Chronic Health Effects:

Ingestion: May cause irritation to the mucous membranes of the digestive system. May result in damage to the liver and kidney, blood disorders and may affect the central nervous system.

Eye: May cause redness, tearing or blurred vision.

Skin: May cause dermatitis and eczema.

Inhaled: Vapour concentrations above exposure limits may cause irritation to the mucous membranes of the respiratory system. May result in damage to the liver and kidney, blood disorders and may affect the central nervous system.

ECOLOGICAL INFORMATION

Prevent the entry of this product and any chemically contaminated water into drains. Dispose of any contaminated water and soil in accordance with the relevant waste management authority.

DISPOSAL CONSIDERATIONS

Contact the relevant waste management authority. Normally suitable for incineration by an approved agent.

TRANSPORT INFORMATION

| | | | |
|-----------------|-------|------------------|-------|
| UN Number: | 1263 | DG Class: | 3 |
| Shipping Name: | PAINT | Subsidiary Risk: | |
| Packaging Group | II | Hazchem | 3[Y]E |

REGULATORY INFORMATION

Poisons Schedule: Schedule 6

OTHER INFORMATION

Date of Issue: 21/10/08
Replaces Issue Dated: 02/11/07

The above information has been presented in good faith and is accurate to the best of our knowledge, at the time of preparation. All of the information supplied herein is related only to the health and safety issues of the product. Users should assume all responsibility for its use, as the conditions under which this product is used are beyond our control. For technical information on the use of this product users should consult the appropriate Technical Data Sheet.

END OF MSDS