



MATERIAL SAFETY DATA SHEET

IDENTIFICATION

PRODUCT(S): LIGHT RUST & METAL CONDITIONER

Supplier: Concept Paints
Address: Lot 40 Charles Street St Marys 2760
Telephone Number: +61 2 96732555
Emergency Telephone: +61 2 96732555 (Monday to Friday 8am to 5pm)
Recommended Use: Automotive Refinish

HAZARDS IDENTIFICATION

Classification:

- HAZARDOUS SUBSTANCE.
- DANGEROUS GOODS.
- IRRITANT.

According to the criteria of ASCC/NOHSC and the ADG Code.

Risk Phrases: R36/38 Irritating to eyes and skin.

Safety Phrases: S9 Keep in a well-ventilated place. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28 After contact with skin, wash with plenty of soap and water. S29 Do not empty into drains. S33 Take precautionary measures against static discharge. S37/39 Wear suitable gloves and eye/face protection. S45 In the case of accident or if you feel unwell, seek medical advice immediately.

INGREDIENTS

Chemical Entity / Hazardous Component	CAS Numbers	Proportion by wt.
Acetone	67-64-1	10 - <30%
Phosphoric Acid	7664-38-2	10 - <30%

This product(s) also contains other ingredients, that are not classified as hazardous by ASCC/NOHSC criteria.

FIRST AID MEASURES

Route of Exposure First Aid Measures

Ingestion: Give a glass of water. Do NOT induce vomiting. Place patients head downwards if vomiting occurs, to prevent it entering lungs .As aspiration of material into lungs can be fatal, causing chemical pneumonitis. Seek medial aid.

Eye: Immediately irrigate with large quantities of water for at least 15 minutes. Seek medical advice.

Skin: Wash exposed area thoroughly with soap and water. Remove contaminated clothing.

Inhaled: Give fresh air, careful not to become a casualty yourself. Remove and loosen clothing. If breathing normally make patient comfortable and keep warm till recovered. If breathing is difficult ensure airways are clear and have a qualified person give oxygen from a face mask. If breathing has stopped commence (EAR), if cardiac arrest commence (CPR) and seek medical aid urgently.

Advice To Doctor: Treat Symptomatically.

FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Not considered a fire hazard. Water spray may be used to keep fire exposed containers cool.

Hazards from Combustion Products: Not prone to combustion. However, Phosphorus Oxides may form when heated to decomposition.

Precautions for Firefighters: Not considered to be a fire hazard. If safe to do so, remove containers from the path of the fire and keep cool with water spray.

Firefighters should wear self contained breathing apparatus with a full face and operated in the positive pressure mode.

Hazchem Code: 3[X]

ACCIDENTAL RELEASE MEASURES

Emergency Procedures: In the case of a spill, ventilate the area and wear the correct Personal Protective Equipment. Neutralise with alkaline material (lime, soda ash).

Containment: Contain and absorb the spill with absorbent material such as sand, soil or vermiculite. Prevent its entry into drains. Transfer the material into drums. Seal and label the drums. Contact the appropriate waste management authority for disposal.

HANDLING AND STORAGE

Handling: Wear the correct Personal Protective Equipment when using this product. Only use in a well ventilated area and apply the product in a spray paint booth with an adequate exhaust system.

Never eat, drink or smoke whilst handling this product. Always wash hands before smoking, eating, drinking or using the toilet.

Safe Storage: Store containers in a cool place and out of direct sunlight. Store in a well ventilated area and away from incompatible materials, oxidising agents and/or foodstuffs. Keep containers tightly closed when not in use and check regularly for leaks.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:	TLV –TWA (mg/m ³)
Acetone	1185
Phosphoric Acid	1

Engineering Controls: Ensure sufficient ventilation to maintain concentration below exposure standard. Only use in a well ventilated area and apply the product in a spray paint booth with an adequate exhaust system. Keep containers sealed when not in use. Earth any mixing vessels when using this product.

Personal Protection: Skin contact should be avoided by wearing impervious work clothing, boots and Neoprene or PVC gloves. Eyes should be protected by chemical goggles or safety glasses fitted with side shields. If an inhalation risks exists, an organic vapour respirator or a self contained breathing apparatus with a full face and operated in the positive pressure mode, should be used. Ensure cartridges are correct for the potential air contamination.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear thin liquid.
Odour:	Slight acidic odour.
pH:	1.5
Vapour Pressure:	Not applicable
Vapour Density:	Not Applicable
Boiling Point Range:	95°C
Melting Point:	Not Applicable
Solubility In Water:	100%
Specific Gravity:	0.95 – 1.05
Flammability Limits:	Not Applicable
Flash Point:	Not Applicable

STABILITY AND REACTIVITY

Chemical Stability: Stable under ordinary conditions of use and storage.

Conditions to Avoid: Incompatible materials.

Incompatible Materials: Liberates explosive hydrogen gas when reacting with chlorides and metals. Can react violently with sodium tetrahydroborate. Exothermic reactions with aldehydes, amines, amides, alcohols, glycols, azo-compounds, carbamates, esters, caustics, phenols, cresols, ketones, organophosphates, epoxides, explosives, combustible materials, unsaturated halides, organic peroxides. Phosphoric acid forms flammable gases with sulphides, mercaptans, cyanides and aldehydes. It also forms toxic fumes with cyanides, sulphides, fluorides, organic peroxides and halogenated organics. Mixtures with nitromethane are explosive.

Hazardous Decomposition Products: Not prone to combustion. However, Phosphorus Oxides may form when heated to decomposition.

Hazardous Reactions: See Incompatible Materials.

TOXICOLOGICAL INFORMATION

Acute Health Effects:

- Ingestion:** Can result in headaches, nausea, vomiting and diarrhoea.
- Eye:** Corrosive. Will cause discomfort and may cause redness, eye burns itching or blurred vision.
- Skin:** Corrosive. May cause irritation to skin and burns.
- Inhaled:** Vapour concentrations above exposure limits may be irritating to the eyes and respiratory tract, may cause headaches and dizziness. Prolonged exposure may result in unconsciousness.

Chronic Health Effects:

- Ingestion:** May cause irritation to the mucous membranes of the digestive system. May result in damage to the liver and kidney, blood disorders and may affect the central nervous system.
- Eye:** Corrosive. May cause redness, eye burns, tearing, blurred vision and permanent eye damage.
- Skin:** May cause dermatitis and eczema.
- Inhaled:** Vapour concentrations above exposure limits may cause irritation to the mucous membranes of the respiratory system. May result in damage to the liver and kidney, blood disorders and may affect the central nervous system.

ECOLOGICAL INFORMATION

Prevent the entry of this product and any chemically contaminated water into drains. Dispose of any contaminated water and soil in accordance with the relevant waste management authority.

DISPOSAL CONSIDERATIONS

Contact the relevant waste management authority. Normally suitable for incineration by an approved agent.

TRANSPORT INFORMATION

UN Number:	3066	DG Class:	8
Shipping Name:	PAINT RELATED MATERIAL	Subsidiary Risk:	
Packaging Group	III	Hazchem	3[X]

REGULATORY INFORMATION

Poisons Schedule: Schedule 5

OTHER INFORMATION

Date of Issue: 20/10/08
Replaces Issue Dated: 01/09/03

The above information has been presented in good faith and is accurate to the best of our knowledge, at the time of preparation. All of the information supplied herein is related only to the health and safety issues of the product. Users should assume all responsibility for its use, as the conditions under which this product is used are beyond our control. For technical information on the use of this product users should consult the appropriate Technical Data Sheet.

END OF MSDS