



# TECHNICAL DATA SHEET

## 1K SUBSTRATE FILLER

### PRODUCT DESCRIPTION

This product has been designed to fill scratches caused by light sanding. It adheres to a wide variety of substrates, including original OEM surfaces. It is ready for use, has good flow properties and can be recoated with the entire range of Concept's products.

### PRODUCT AND ADDITIVES

- Concept 1K Substrate Filler




### SUITABLE SUBSTRATES

- Original OEM surfaces.
- OEM electrostatic primers.
- Sound existing surfaces, except for weak surfaces such as nitrocellulose or enamels.

### MIXING RATIO





- Ready For Use.

### SPRAY GUN AND PRESSURE

SPRAY GUN & PRESSURE:	<ul style="list-style-type: none"><li>• Use 1.2 – 1.4mm through a suction feed gun.</li><li>• Pressure at 350 – 450 kPa (Gravity feed is slightly higher pressure).</li></ul>	
-----------------------	---	---

## APPLICATION

- All surfaces must be thoroughly sanded and cleaned with Concept Wax & Grease Remover prior to application.
- Apply one to two even coats.

<b>SPRAYING VISCOSITY:</b>	<ul style="list-style-type: none"> <li>• 17 – 18 seconds B4 cup at 25°C.</li> </ul>	 19-20 SECONDS
<b>FLASH-OFF TIME:</b>	<ul style="list-style-type: none"> <li>• If required, 5 – 10 minutes between coats at 25°C.</li> </ul>	
<b>DRYING:</b>	<ul style="list-style-type: none"> <li>• 15 – 20 minutes at 25°C for a Dry Film Thickness of 7 – 10 Micron.</li> </ul>	
<b>RECOATING:</b>	<ul style="list-style-type: none"> <li>• 5 minutes at 25°C.</li> </ul>	

## TECHNICAL INFORMATION

<b>COLOUR:</b>	Clear
<b>COVERAGE:</b>	20 m <sup>2</sup> /L @ 10 Micron Dry Film Thickness.
<b>PACKAGING:</b>	1LT, 4LT
<b>ITEM CODE:</b>	A03C/1KSUBFIL
<b>SHELF LIFE:</b>	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

**REVISED: 6 October 2005**

**REPLACES ISSUE:**