



TECHNICAL DATA SHEET

2K SATIN WOOD CLEAR

PRODUCT DESCRIPTION

2K Wood Clear is a high performance two pack clear designed specifically to give a smooth satin finish to timber surfaces. It has superior flow, producing a film with exceptional chemical resistance, flexibility and hardness.

PRODUCT AND ADDITIVES

- Concept 2K Satin Wood Clear
- Concept 2K Wood Clear Hardener
- Concept 2K Thinner


SUITABLE SUBSTRATES

- Concept 1K Wood Sealer
- Concept 2K Wood Sealer

MIXING RATIO




- 2 parts Concept 2K Satin Wood Clear by volume.
- 1 part Concept 2K Wood Clear Hardener by volume.
- If needed a 5% reduction can be made with Concept 2K Thinner.

SPRAY GUN AND PRESSURE

SPRAY GUN & PRESSURE:	<ul style="list-style-type: none">• 1.2 – 1.5 mm through a gravity feed gun.• Pressure is 350 – 450 kPa through a gravity feed gun.	
-----------------------	--	---

APPLICATION

- Stir thoroughly before use.
- All surfaces must be thoroughly sanded prior to application. Ensure all surfaces are clean and free from loose particles.
- Apply two to three coats.

SPRAYING VISCOSITY:	<ul style="list-style-type: none"> • 18 – 19 seconds B4 cup at 25°C. 	 <p style="font-size: small; margin-top: 5px;">18 - 19 SECONDS</p>
FLASH-OFF TIME:	<ul style="list-style-type: none"> • 5 – 10 minutes between coats at 25°C. 	
DRYING:	<ul style="list-style-type: none"> • 16 - 24 hours at 25°C for a Dry Film Thickness of 50 – 60 Micron. 	

TECHNICAL INFORMATION

COLOUR:	Hazy
COVERAGE:	8 m ² /L @ 60 Micron Dry Film Thickness.
POT LIFE:	2 – 3 Hours at 25°C
GLOSS:	50% at 60°
PACKAGING:	4LT, 20LT (Hardener: 1LT)
ITEM CODE:	A15/2KSATCLR (Hardener: A15/2KHARD)
SHELF LIFE:	12 Months (Hardener: 6 months)

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 14 September 2006

REPLACES ISSUE: