



TECHNICAL DATA SHEET

BUMPER BAR PAINT

PRODUCT DESCRIPTION

This is a flexible factory pack bumper bar paint, which has been designed specifically for use on bumper bars.

PRODUCT AND ADDITIVES

- Concept Bumper Bar Paint
- Concept Multi-Thinner




SUITABLE SUBSTRATES

- Sound existing finishes.
- New bumper bars primed with Concept Plastic Primer.

MIXING RATIO




- Up to 10% reduction may be required with Concept Multi-Thinner.

SPRAY GUN AND PRESSURE

SPRAY GUN & PRESSURE:	<ul style="list-style-type: none">• 2.0mm tip with a suction feed gun• Pressure is 350 – 400 kPa. (The same condition applies for gravity feed)	
-----------------------	--	---

APPLICATION

- Except for surfaces primed with Concept Plastic Primer, all other surfaces must be thoroughly sanded and cleaned with Concept Wax & Grease Remover prior to application.
- Apply two to three even coats.

SPRAYING VISCOSITY:	<ul style="list-style-type: none"> • 18 – 20 seconds B4 cup at 25°C. 	
FLASH-OFF TIME:	<ul style="list-style-type: none"> • 5 minutes between coats at 25°C. 	
DRYING:	<ul style="list-style-type: none"> • 2 – 3 hours at 25°C for a Dry Film Thickness of 40 – 50 Micron. 	

TECHNICAL INFORMATION

COLOUR:	Black or Grey
COVERAGE:	3 m ² /L @ 50 Micron Dry Film Thickness.
GLOSS:	Satin
PACKAGING:	1LT, 4LT
ITEM CODE:	A03D/BUMP
SHELF LIFE:	12 Months

The above information is reliable and accurate to the best of our knowledge at the time of preparation. Any recommendations or suggestions made are without warranty or guarantee. Users assume all responsibility since the conditions of use are beyond our control.

REVISED: 1 December 2004

REPLACES ISSUE: 1 July 2003