

# Technical Data Sheet

Product Name	
Full Product Name	<b>MS-22 2K Clear</b>
Type of Product	2K acrylic urethane clear coat
Description	<b>Concept MS-22 2K Clear</b> is a <b>medium to high solids, high-performance 2K clear coat</b> specifically designed for basecoat systems. It delivers superior flow and levelling, producing an exceptionally high-gloss finish with outstanding chemical resistance, durability, and hardness.

Products						
Product Name	Volume Solids %	Weight Solids %	Density		VOC	
			g/mL	lbs/US gal	g/L	lbs/US gal
MS-22 2K Clear	43.0	39.7	0.990	8.26	507.4	4.23
MS-22 Hardener Slow	43.0	49.3	1.013	8.45	512.8	4.28
MS-22 Hardener	42.8	49.3	1.007	8.41	509.9	4.26
MS-22 Hardener Fast	41.9	48.4	1.005	8.39	517.7	4.32
MS-22 Hardener Extra Fast	41.0	47.5	1.002	8.36	525.2	4.38
2K Thinner Slow	0.0	0.0	0.893	7.45	892.7	7.45
2K Thinner	0.0	0.0	0.882	7.36	881.9	7.36
2K Thinner Fast	0.0	0.0	0.872	7.27	871.5	7.27

Properties
<ul style="list-style-type: none"> <li>Medium to high solids 2K clear coat</li> <li>Excellent flow and levelling</li> <li>Very high gloss finish</li> <li>Excellent chemical resistance and durability</li> </ul>

## Substrates

- Concept No Mix Basecoat System colours
- Concept Unicolour 900 Basecoat System colours
- Sound existing surfaces, except for unstable surfaces such as nitrocellulose or enamels

## Substrate Preparation














### All Substrates

All surfaces must be clean and free from any contamination prior to application.

# Technical Data Sheet

## Product Preparation

	<b>Mixing Ratio</b> 2:1 (by volume)		<b>Concept MS-22 2K Clear</b>	<b>Concept MS-22 Hardener</b>	
			2 parts	1 part	
	<b>Reducer</b>	Up to 5% (v/v) of Concept 2K Thinner, if required.			
	<b>Pot life</b> @ 25°C (77°F)	6-8 hours			
	<b>Spray viscosity</b> @ 25°C (77°F)	<b>BSB 4 Cup</b> <b>Ford 4 Cup</b>	18-19 s 16-17 s		
  	<b>Spray equipment</b>	<b>Gun type</b>	<b>Fluid tip</b>	<b>Spray pressure</b>	<b>Spray Distance</b>
		<b>Gravity feed</b>	1.3-1.4 mm 0.051-0.055"	200-240 kPa 2.0-2.4 bar 30-35 psi	15-20 cm 6-8 inch
		<b>Suction feed</b>	1.3-1.4 mm 0.051-0.055"	200-240 kPa 2.0-2.4 bar 30-35 psi	15-20 cm 6-8 inch
		<b>HVLP</b>	1.2-1.3 mm 0.047-0.051"	40-70 kPa 0.4-0.7 bar 6-10 psi	15-20 cm 6-8 inch
	<b>Number of coats</b>	2	Apply two even full coats. Avoid heavy wet coats.		
	<b>DFT Recommended</b>	40-50 µm 1.6-2.0 mils			
	<b>Flash off time</b> @ 25°C (77°F)	5-10 min between coats			
	<b>Drying</b>	<b>Air Dry</b> @ 25°C (77°F)	12-16 hours		
		<b>Low Bake</b> @ 50°C (122°F)	30-40 min		

This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.

Date: 21<sup>st</sup> October 2016

# Technical Data Sheet

Version:01

## Remarks



Stir all products thoroughly each time before use.  
Stir the mixture well after the weigh-out of the components.



Surface temperature must always be a minimum of 3°C  
(5°F) above dew point.

## Equipment Cleaning

Use recommended Concept Paints cleaner

## Dry Film Properties

After 7 days drying,  
**when compared to similar technology products.**

Gloss

High

Flexibility

Excellent

Durability

Excellent

Chemical Resistance and  
Hardness

Excellent

## Product Data

Colour

Water white

Theoretical Coverage

Approx. 7.0 m<sup>2</sup>/L (285 ft<sup>2</sup>/US gal) @ recommended DFT

Shelf Life

36 months in an unopened container  
at room temperature, away from sunlight.

## Product Packaging

Product Code 1	Product Name	Package Size
AU7229000000X	MS-22 2K Clear	1L, 5L, 15L(Kitx3)
AU7229100000X	MS-22 Hardener Slow	2.5L
AU7229200000X	MS-22 Hardener	500 mL, 2.5L
AU7229300000X	MS-22 Hardener Fast	500 mL, 2.5L
AU72294002.50	MS-22 Hardener Extra Fast	2.5L
AU8319100000X	2K Thinner Slow	1L, 4L, 20L
AU8319200000X	2K Thinner	1L, 4L, 20L
AU8319300000X	2K Thinner Fast	1L, 4L, 20L

## Safety

For automotive and industrial use only by professional painters. Not recommended for sale to, or use by the general public. Before using, read and follow all label and Safety Data Sheet (SDS) precautions. If mixed with other components, the mixture will have hazards of all individual components.

Read and understand the Guidelines for the Safe Handling and Use of Isocyanate Containing Paints, including the use of approved respiratory protection and Personal Protective Equipment. Use only in a well-ventilated approved spray booth, according to local regulations.

The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check if the information is current, and the product is suitable for its intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved.

We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

This Technical Data Sheet supersedes all previous issues.

Concept Paints  
26-30 Charles Street  
St Marys NSW 2760  
Sydney, Australia

ph. +61 (2) 9673 2555  
fax. +61 (2) 9623 1918  
info@conceptpaints.com.au  
www.conceptpaints.com.au