

Safety Data Sheet



Driven by Innovation

NON-Hazardous, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: No Mix Basecoat System

Synonyms

NM-01 Black
NM-02 Blue
NM-03 Bright Blue
NM-04 Bright Gold
NM-05 Bright Red
NM-06 Custard
NM-07 Copper
NM-08 Vivid Magenta
NM-09 Raven Black
NM-10 Deep Black
NM-11 Cobalt Blue
NM-12 Maroon
NM-13 Deep Maroon
NM-14 Garnet
NM-15 Green
NM-16 Green Blue
NM-17 Green Gold
NM-18 Grey Black
NM-19 Empress Black
NM-20 Light Red Oxide
NM-21 Lime
NM-22 Magenta
NM-23 Midnight Blue
NM-24 Red Gold
NM-25 Red Maroon
NM-26 Vivid Orange
NM-27 Ruby
NM-28 Turquoise
NM-29 Midnight Black
NM-30 Violet
NM-31 White
NM-32 Yellow Gold
NM-33 Yellow Ochre
NM-34 Special Violet
NM-35 Port Wine Red
NM-36 Deep Blue
NM-37 Special Deep Black
NM-38 Special Red Maroon
NM-39 HS Special Red
NM-40 Royal Blue
NM-41 Reduced Black
NM-42 Silk Silver
NM-43 Silk Russet
NM-44 Silk Gold
NM-45 Silk Blue
NM-46 Silk Red
NM-47 Silk Green
NM-48 Silk Copper
NM-51 Red Yellow
NM-52 Topaz
NM-53 Organic Orange
NM-54 Special Silver Bright Fine

Product Code

AU50000010001
AU50000020001
AU50000030001
AU50000040001
AU50000050001
AU50000060.25
AU50000070001
AU50000080.25
AU50000090001
AU50000100001
AU50000110001
AU50000120001
AU50000130001
AU50000140001
AU50000150001
AU50000160001
AU50000170.25
AU50000180.25
AU50000190001
AU50000200001
AU50000210001
AU50000220001
AU50000230001
AU50000240001
AU50000250001
AU50000260.25
AU50000270.25
AU50000280001
AU50000290001
AU50000300001
AU50000310001
AU50000320001
AU50000330001
AU50000340001
AU50000350001
AU50000360001
AU50000370001
AU50000380001
AU50000390001
AU50000400001
AU50000410001
AU50000420001
AU50000430001
AU50000440001
AU50000450001
AU50000460001
AU50000470001
AU50000480001
AU50000510001
AU50000520001
AU50000530001
AU50000540001

Safety Data Sheet



Driven by Innovation

NM-55 Special Silver Coarse	AU50000550001
NM-56 Silver Dollar Bright Coarse	AU50000560001
NM-57 Silver Dollar Bright Fine	AU50000570001
NM-59 Metallic Additive	AU50000590001
NM-60 Stabiliser Additive	AU50000600001
NM-61 Effect White	AU50000610001
NM-62 HS Special White	AU50000620001
NM-63 HS Special Yellow	AU50000630001
NM-65 Fine Metallic	AU50000650001
NM-66 Medium Metallic	AU50000660001
NM-67 Coarse Metallic	AU50000670001
NM-68 Extra Fine Silver	AU50000680001
NM-69 Fine Silver	AU50000690001
NM-70 Silver	AU50000700001
NM-71 Medium Silver	AU50000710001
NM-72 Coarse Silver	AU50000720001
NM-74 Coarse Aluminium	AU50000740001
NM-75 Extra Coarse Aluminium	AU50000750001
NM-77 Fine White Pearl	AU50000770001
NM-78 White Sparkle Pearl	AU50000780001
NM-79 Bright Silver Pearl	AU50000790.25
NM-80 Yellow Pearl	AU50000800001
NM-82 Fine Yellow Gold Pearl	AU50000820001
NM-83 Orange Pearl	AU50000830001
NM-86 Copper Pearl	AU50000860001
NM-87 Bright Russet Pearl	AU50000870001
NM-88 Fine Russet Pearl	AU50000880001
NM-89 Blue Russet Pearl	AU50000890.25
NM-90 Red Blue Pearl	AU50000900001
NM-91 Fine Blue Pearl	AU50000910001
NM-92 Green Blue Pearl	AU50000920001
NM-93 Fine Green Pearl	AU50000930001
NM-95 Blue Green Pearl	AU50000950001
NM-96 Red Pearl	AU50000960001
NM-97 Fine Silver Pearl	AU50000970001
NM-98 Fine Violet Pearl	AU50000980001
NM-99 Metallic Raiser	AU50000990001
NM-101 Red Candy	AU50001010.25
NM-102 Brandywine Candy	AU50001020.25
NM-103 Yellow Candy	AU50001030.25
NM-104 Green Candy	AU50001040.25

Recommended use: Automotive Refinish

Supplier: GPI Automotive (NZ) Ltd
Company No.: 455504
Street Address: 59 Greenmount Drive,
East Tamaki, Auckland,
New Zealand, 2013
Telephone: +64 9 274 4943
Email: info@conceptpaints.com.au

Emergency Telephone number: +1 703 741 6037 (24 Hours)

2. HAZARDS IDENTIFICATION

Based on available information, this material is not classified as hazardous according to criteria of EPA New Zealand.

Safety Data Sheet



Driven by Innovation

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
n-Butyl Acetate	123-86-4	>60 % (w/w)
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	30-60 % (w/w)
2-Butanone	78-93-3	30-60 % (w/w)
Titanium oxide (TiO ₂)	13463-67-7	30-60 % (w/w)
Acetone	67-64-1	30-60 % (w/w)
2-Propanol, 1-methoxy-, acetate	108-65-6	10-30 % (w/w)
Solvent naphtha, petroleum, light aromatic	64742-95-6	10-30 % (w/w)
Xylene	1330-20-7	<10 % (w/w)
Aluminium	7429-90-5	<10 % (w/w)
Mica group minerals	12001-26-2	<10 % (w/w)
Iron oxide (Fe ₂ O ₃)	1309-37-1	<10 % (w/w)
Carbon black	1333-86-4	<10 % (w/w)
Propanoic acid, 3-ethoxy-, ethyl ester	763-69-9	<10 % (w/w)
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	<10 % (w/w)
Naphtha, petroleum, hydrotreated heavy	64742-48-9	<10 % (w/w)
Graphite	7782-42-5	<10 % (w/w)
1-Butanol	71-36-3	<10 %
Benzenepropanoic acid, 3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxy-, C7-9-branched and linear alkyl esters	127519-17-9	<10 %
Benzene, ethyl-	100-41-4	<10 %
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[N-(4-chloro-2,5-dimethoxyphenyl)-3-oxo-	5567-15-7	<10 %
Copper, [1-[(2-hydroxyphenyl)imino]methyl]-2-naphthalenolato(2-)-N,O,O']-	15680-42-9	<10 %
Ingredients determined to be Non-Hazardous		Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Safety Data Sheet



Driven by Innovation

PPE for First Aiders: Wear rubber boots, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from neoprene, polyvinyl chloride (PVC) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3YE

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and/or the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

Safety Data Sheet



	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
2-Butanone (Methyl ethyl ketone, MEK)	150	445	300	890	(bio)
Acetone	500	1,185	1,000	2,375	(bio)
Aluminium, as Al (Alkyls - not otherwise classified)		2			
Aluminium, as Al (Metal dust)		10			
Aluminium, as Al (Pyro powders)		5			
Aluminium, as Al (Soluble salts)		5			
Aluminium, as Al (Welding fumes)		5			
Carbon black		3			6.7B
Ethyl benzene	100	434	125	543	
Graphite, all forms except graphite fibres (Respirable dust containing <1% free silica)		3			
Iron oxide dust and fume (Fe ₂ O ₃), as Fe		5 (w)			
Mica (Respirable dust)		3			
n-Butyl acetate	150	713	200	950	
n-Butyl alcohol	Ceiling 50	Ceiling 150			(skin)
Titanium dioxide		10			
Xylene (o-, m-, p-isomers) (Dimethylbenzene)	50	217			

As published by WorkSafe New Zealand.

WES-TWA (Workplace Exposure Standard - Time-weighted average). The average airborne concentration of a substance calculated over an eight-hour working day.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded at any time during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-term exposure limit). The 15-minute time weighted average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Exposures at concentrations between the WES-TWA and the WES-STEL should be less than 15 minutes, should occur no more than four times per day, and there should be at least 60 minutes between successive exposures in this range.

6.7B - Suspected carcinogen. Carcinogen—suspected human carcinogen: data indicates limited evidence in humans or animals that exposure to the substance may lead to the development of cancer, or an increased incidence of tumours.

(skin) - Skin absorption. Skin absorption—applicable to a substance that is capable of being significantly absorbed into the body through contact with the skin.

(bio) - Exposure can also be estimated by biological monitoring.

(w) - A range of airborne contaminants are associated with gas and arc welding. The type of metal being welded, the electrode employed and the welding process will all influence the composition and amount of fume. Gaseous products such as oxides of nitrogen, carbon monoxide and ozone may also be produced. In the absence of specific substances such as chromium, and where conditions do not support the generation of toxic gases, the fume concentration inside the welder's helmet should not exceed 5 mg/m³.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during

Safety Data Sheet



Driven by Innovation

product manufacture.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

Personal Protection Equipment: RUBBER BOOTS, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear rubber boots, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from neoprene, polyvinyl chloride (PVC) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Viscous Liquid
Colour: Multi Coloured
Odour: Strong Solvent Odour

Specific Gravity: 0.90 – 1.40
Vapour Pressure (20 °C): 24.7 kPa @ 20°C
Flash Point (°C): -18 (Open Cup)
Flammability Limits (%): 1 (LEL) by volume - 13 (UEL) by volume
Autoignition Temperature (°C): 354
Boiling Point/Range (°C): 55 – 175
Viscosity: <8,000cps
Evaporation Rate (n-Butyl acetate=1): 0.12 – 6.30

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

Safety Data Sheet



Driven by Innovation

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin may result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: May be an eye irritant.

Acute toxicity

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 20.0 mg/L for vapours or LC50 > 5.0 mg/L for dust and mist or LC50 > 5,000 ppm gas

Skin contact: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5,000 mg/Kg bw

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5,000 mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation):

This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K_{ow} < 4.

Safety Data Sheet



Driven by Innovation

Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 1263
Dangerous Goods Class: 3
Packing Group: II
Hazchem Code: •3YE
Emergency Response Guide No: 14

Proper Shipping Name: PAINT

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.



Safety Data Sheet



Driven by Innovation

UN No: 1263
Dangerous Goods Class: 3
Packing Group: II

Proper Shipping Name: PAINT

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1263
Dangerous Goods Class: 3
Packing Group: II

Proper Shipping Name: PAINT

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)
• Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish

16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.