

<b>Product Name</b>	
Full Product Name	<b>Tyre Black</b>
Type of Product	1K brushing tyre enamel
Description	Concept Tyre Black is a very fast drying brushing enamel, specifically designed to enhance the appearance of tyres. It is characterised by its excellent flow properties and appearance.

<b>Products</b>						
Product Name	Volume Solids %	Weight Solids %	Density		VOC	
			g/mL	lbs/US gal	g/L	lbs/US gal
Tyre Black - Glossy	34.4	41.1	0.942	7.86	554.9	4.63
Tyre Black - Matt	6.2	9.6	0.864	7.21	781.0	6.52

<b>Properties</b>
<ul style="list-style-type: none"> <li>• Ready for use</li> </ul>
<ul style="list-style-type: none"> <li>• Good flow and appearance</li> </ul>
<ul style="list-style-type: none"> <li>• Very fast drying</li> </ul>

<b>Substrates</b>
<ul style="list-style-type: none"> <li>• New or previously painted tyres</li> </ul>

<b>Substrate Preparation</b>	
 <b>All Substrates</b>	Tyres must be thoroughly washed prior to application.

## Product Preparation

	<b>Reducer</b>	Not required – product supplied ready for use.	
	<b>Pot life</b> @ 25°C (77°F)	N/A	
	<b>Spray viscosity</b> @ 25°C (77°F)	<b>BSB 4 Cup</b> <b>Ford 4 Cup</b>	As is
	<b>Application</b>	Using a brush, apply one even full coat.	
	<b>DFT Recommended</b>	10-15 µm 0.4-0.6 mil	
	<b>Flash off time</b> @ 25°C (77°F)	N/A	
	<b>Drying</b>	<b>Air Dry</b> @ 25°C (77°F)	10-20 min

This data relates only to the material designated herein and does not apply to use in combination with any other material or any process. The data is not to be considered as a warranty or quality specification and we assume no liability in connection with its use.

## Remarks

	Stir all products thoroughly each time before use. Stir the mixture well after the weigh-out of the components.
	Surface temperature must always be a minimum of 3°C (5°F) above dew point.

## Equipment Cleaning

Use recommended Concept Paints 035 Gunwash

## Dry Film Properties

After 7 days drying,  
**when compared to similar technology products.**

<b>Gloss</b>	Full gloss or matt
--------------	--------------------

# Technical Data Sheet

Product Data	
Colour	Black
Theoretical Coverage	Approx. 4.0 m <sup>2</sup> /L (160 ft <sup>2</sup> /US gal) @ recommended DFT
Shelf Life	36 months in an unopened container at room temperature, away from sunlight.

Product Packaging		
Product Code	Product Name	Package Size
AU4667018000X	Tyre Black - Glossy	1L, 4L
AU46670170001	Tyre Black - Matt	1L

Safety
<p>For automotive and industrial use only by professional painters. Not recommended for sale to, or use by the general public. Before using, read and follow all label and Safety Data Sheet (SDS) precautions. If mixed with other components, the mixture will have hazards of all individual components.</p> <p>Read and understand the Guidelines for the Safe Handling and Use of Isocyanate Containing Paints, including the use of approved respiratory protection and Personal Protective Equipment. Use only in a well-ventilated approved spray booth, according to local regulations.</p>

The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check if the information is current and the product is suitable for its intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved.

We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

This Technical Data Sheet supersedes all previous issues.

Concept Paints  
26-30 Charles Street  
St Marys NSW 2760  
Sydney, Australia

ph. +61 (2) 9673 2555  
fax. +61 (2) 9623 1918  
office@conceptpaints.com.au  
www.conceptpaints.com.au